

B VISSION

Securing Bharat in One Vission

IP Dome Camera

Model: BV-KT4IPDC

Category: IP Camera

Technical Specifications

Parameter	Specification
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	4mp (2560 x 1440)
Min. Illumination	Color: 0.001 Lux @(F2.0, AGC ON), 0 Lux with white light
Shutter Speed	1/3 s to 1/100, 000 s
Focal Length & FOV	4 mm, horizontal FOV 75.2°, vertical FOV 40.8°, diagonal FOV 88.3°
Focus	Fixed
Smart Supplement White Light	Up to 30 m
IR Range	Up to 40 m
Main Stream	25 fps (2560 × 1440, 1920 x 1080)
Sub-Stream	25 fps (720 × 480)
Video Compression	H.265/H.264
Video Bit Rate	32 Kbps to 8 Mbps
Audio Compression	G.711a
Audio Bit Rate	64 Kbps
Audio Sampling Rate	8 kHz
Simultaneous Live View	Up to 5 channels
API	Open Network Video Interface
Web Browser	Chrome, Firefox, Edge. All latest version
Image Settings	Brightness, Sharpness, Color contrast, Saturation, 3D noise reduction, Exposu...
Day/Night Switch	Day, Night, Auto, Schedule
Wide Dynamic Range (WDR)	Yes
Connection Protocol	Onvif
Ethernet Interface	1 RJ45 10 M/100 M Ethernet port
Storage	Built-in memory card slot, support external microSD card, up to 256 GB
Built-in Microphone	Yes

Built-in Speaker	Yes
Hardware Reset	Yes
Basic Event	Motion detection, Human Shape detection, Sound detection
Smart Event	Alert Alaram(alert area, alert period setting)
Linkage	Upload to memory card
Storage Conditions	-30 °C to 55 °C (-22 °F to 131 °F). Humidity: 95% or less (non-condensing)
Startup and Operating Conditions	-30 °C to 55 °C (-22 °F to 131 °F). Humidity: 95% or less (non-condensing)



B Vission - Krishnaa Technologies | Made in India
Website: www.krishnaa.co.in | Phone: +91 89062 29767